

CKKB - B 系列低压并联电容器

| 型号规格<br>About Mode | 额定电压 | 额定容量 | 额定电流  | 额定电容   | 圆柱型外形<br>尺寸 | 方箱型外形<br>尺寸 |
|--------------------|------|------|-------|--------|-------------|-------------|
|                    | Un   | Qn   | In    | Cn     |             |             |
|                    | V    | Var  | A     | μF     | ΦD*H        | A*B*H       |
| CKKB250V 系列        |      |      |       |        |             |             |
| CKKB250-5-3        | 250  | 5    | 11.5  | 254.8  | Φ86*240     | /           |
| CKKB250-10-3       |      | 10   | 23.1  | 509.6  | Φ86*240     | /           |
| CKKB250-15-3       |      | 15   | 34.6  | 764.3  | Φ116*250    | /           |
| CKKB250-20-3       |      | 20   | 46.2  | 1019.1 | Φ116*250    | /           |
| CKKB250-25-3       |      | 25   | 57.7  | 1273.9 | Φ136*250    | 280*95*320  |
| CKKB250-30-3       |      | 30   | 69.3  | 1528.7 | Φ136*250    | 280*95*360  |
| CKKB250-40-3       |      | 40   | 92.4  | 2038.2 | /           | 310*105*360 |
| CKKB250-50-3       |      | 50   | 115.5 | 2547.8 | /           | 370*125*320 |
| CKKB250-60-3       |      | 60   | 138.6 | 3057.3 | /           | 370*125*360 |
| CKKB415V 系列        |      |      |       |        |             |             |
| CKKB415-10-3       | 415  | 10   | 13.9  | 184.9  | Φ86*240     | /           |
| CKKB415-15-3       |      | 15   | 20.9  | 277.4  | Φ86*240     | /           |
| CKKB415-20-3       |      | 20   | 27.8  | 369.8  | Φ96*250     | /           |
| CKKB415-25-3       |      | 25   | 34.8  | 462.3  | Φ116*250    | /           |
| CKKB415-30-3       |      | 30   | 41.7  | 554.8  | Φ136*250    | /           |
| CKKB415-40-3       |      | 40   | 55.7  | 739.7  | /           | 310*105*320 |
| CKKB415-50-3       |      | 50   | 69.6  | 924.6  | /           | 310*105*320 |
| CKKB415-60-3       |      | 60   | 83.5  | 1109.5 | /           | 370*125*360 |
| CKKB440V 系列        |      |      |       |        |             |             |
| CKKB440-10-3       | 440  | 10   | 13.1  | 164.5  | Φ86*240     | /           |
| CKKB440-15-3       |      | 15   | 19.7  | 246.7  | Φ86*240     | /           |
| CKKB440-20-3       |      | 20   | 26.2  | 329    | Φ96*250     | /           |
| CKKB440-25-3       |      | 25   | 32.8  | 411.2  | Φ116*250    | /           |
| CKKB440-30-3       |      | 30   | 39.4  | 493.5  | Φ136*250    | /           |
| CKKB440-40-3       |      | 40   | 52.5  | 658    | /           | 310*105*320 |
| CKKB440-50-3       |      | 50   | 65.6  | 822.5  | /           | 370*125*320 |
| CKKB440-60-3       |      | 60   | 78.7  | 987.0  | /           | 370*125*260 |
| CKKB450V 系列        |      |      |       |        |             |             |
| CKKB450-10-3       | 450  | 10   | 12.8  | 157.3  | Φ86*240     | /           |
| CKKB450-15-3       |      | 15   | 19.3  | 235.9  | Φ86*240     | /           |
| CKKB450-20-3       |      | 20   | 25.7  | 314.5  | Φ96*250     | /           |
| CKKB450-25-3       |      | 25   | 32.1  | 393.2  | Φ116*250    | /           |
| CKKB450-30-3       |      | 30   | 38.5  | 471.5  | Φ116*250    | /           |
| CKKB450-40-3       |      | 40   | 51.3  | 629.1  | /           | 310*105*320 |
| CKKB450-50-3       |      | 50   | 64.2  | 786.4  | /           | 370*125*320 |
| CKKB450-60-3       |      | 60   | 77.0  | 943.6  | /           | 370*125*360 |
| CKKB480V 系列        |      |      |       |        |             |             |
| CKKB480-10-3       | 480  | 10   | 12.0  | 138.2  | Φ86*240     | /           |
| CKKB480-15-3       |      | 15   | 18.0  | 207.3  | Φ86*240     | /           |
| CKKB480-20-3       |      | 20   | 24.1  | 276.5  | Φ96*250     | /           |
| CKKB480-25-3       |      | 25   | 30.1  | 345.6  | Φ116*250    | /           |
| CKKB480-30-3       |      | 30   | 36.1  | 414.7  | Φ136*250    | /           |
| CKKB480-40-3       |      | 40   | 48.1  | 552.9  | /           | 310*105*320 |
| CKKB480-50-3       |      | 50   | 60.1  | 691.1  | /           | 370*125*320 |
| CKKB480-60-3       |      | 60   | 72.2  | 829.4  | /           | 370*125*360 |
| CKKB525V 系列        |      |      |       |        |             |             |
| CKKB525-10-3       | 525  | 10   | 11.0  | 115.6  | Φ86*240     | /           |
| CKKB525-15-3       |      | 15   | 16.5  | 173.3  | Φ86*240     | /           |
| CKKB525-20-3       |      | 20   | 22.0  | 231.1  | Φ96*250     | /           |
| CKKB525-25-3       |      | 25   | 27.5  | 288.9  | Φ136*250    | /           |
| CKKB525-30-3       |      | 30   | 33.0  | 346.6  | /           | /           |
| CKKB525-40-3       |      | 40   | 44.0  | 462.2  | /           | 310*105*320 |
| CKKB525-50-3       |      | 50   | 55.0  | 577.7  | /           | 370*125*320 |
| CKKB525-60-3       |      | 60   | 66.0  | 693.3  | /           | 370*125*360 |
| CKKB690V 系列        |      |      |       |        |             |             |
| CKKB690-10-3       | 690  | 10   | 8.4   | 66.9   | Φ86*240     | /           |
| CKKB690-15-3       |      | 15   | 12.6  | 10300  | Φ86*240     | /           |
| CKKB690-20-3       |      | 20   | 16.7  | 133.8  | Φ96*250     | /           |
| CKKB690-25-3       |      | 25   | 20.9  | 167.2  | Φ116*250    | /           |
| CKKB690-30-3       |      | 30   | 25.1  | 200.7  | Φ136*250    | /           |
| CKKB690-40-3       |      | 40   | 33.5  | 267.6  | /           | 310*105*320 |
| CKKB690-50-3       |      | 50   | 41.8  | 334.5  | /           | 370*125*320 |
| CKKB690-60-3       |      | 60   | 50.2  | 401.4  | /           | 370*125*360 |